



### Design

The AGSR series product is designed to compliment traditional architectural forms with traditional curvilinear styling, while the segmented optics provides enhanced illumination. A decorative reveal in the housing provides additional styling.

### Applications

Area and site applications of all sizes, including but not limited to: commercial parking areas, shopping/retail/mall developments, etc.

### Construction

Durable 20"/25"/29" dia. round spun aluminum housing combined with a heavy cast aluminum door frame. Single tool access for ease of maintenance.

### Certification

ETL/cETL listed luminaire, suitable for wet location.

Series	Distribution	Voltage	Mounting	Options*	Finish
Pulse Start MH	20" Vertical	120	Arm Mount - SQ/RD	F1 (single fuse 120/277)	Smooth Powder
AGSR20P-70	Optics	208	S2.5	F2 (dbl fuse 208/240/480)	SA (satin alum.)
AGSR20P-100	(flat glass standard - full cutoff)	240	(2.5" arm - 1@90, 2@90, 3@120)	TLR (twist lock receptacle)	DB (dark bronze)
AGSR20P-150	V	277		GSL (glass sag lens)	BLK (black)
AGSR20P-175		480	\$13.5	SK (external house shield)	WHT (white)
AGSR20P-200	20" Horizontal		(13.5" arm - 2,3,4@90)		GR (gray)
AGSR25P-250	Optics				
AGSR25P-400	(flat glass standard - full cutoff)				
AGSR29P-400	3		Horizontal Fitter		Special
AGSR29P-450	F		HSF (mounts to 2 3/8" OD)		RAL(*) (*specify #)
AGSR29P-875	25"-29" Vertical				
AGSR29P-1000	Optics		Post Top Mount		
	(flat glass standard - full cutoff)		PT (requires 2 3/8" OD tenon)		
High Pressure Sodium	VS				
AGSR20S-70	VR		Wall Bracket		
AGSR20S-100	25"-29" Horizontal		SC (cast wall bracket)		
AGSR20S-150	Optics				
AGSR25S-250	(flat glass standard - full cutoff)				
AGSR25S-400	3				
AGSR29S-400	F				
AGSR29S-750	(*1000HPS VR/VS				
AGSR29S-1000	requires convex lens)				
	(*25" 250-400HPS				
	requires convex lens)				

Refer to spec sheet for additional details, available accessories, and specific ordering information. (\*some options may not be available in some configurations)